

THE "ULTRA COMPACT"

XP-3TRAC=

FLUX RECOVERY SYSTEM

LIGHTWEIGHT, VERY COMPACT, RUGGED AND POWERFUL; THE XP3TRAC MOUNTS EASILY ONTO MOST AUTOMATIC SUBMERGED ARC WELDING TRACTORS. ALSO IDEAL FOR OTHER APPLICATIONS WHERE SIZE AND WEIGHT ARE IMPORTANT FACTORS. XP-3TRAC

SPECIFICATIONS:

- Weight Empty: 12lbs (5.4Kg); total added wt. = 9 lbs. (4 kg) i.e., because Lincoln hopper is removed.
- Dimensions: 18"(45.7cm)H X 10"(25.4cm)W X 8"(20.3cm)D
- Input Power: Clean and dry, compressed air @70-100 psi (5-7 bar) @ 8 cfm (226 L/min.) No electric input required.
- Comes Complete with 5ft. (1.5 m) hose, nozzle, mounting brackets for XP-3TRAC and hose mounting bracket... ready for installation!

XP-3TRAC mounted on Lincoln LT-7 tractor in butt weld position. This system represents standard XP-3TRAC packaging which includes NZ-1 nozzle, FHM-1 hose bracket, 5 ft. (1.5m) 1-1/2" (3.81 cm) hose, mounting bracket for XP-3TRAC to LT-7 and XP-3TRAC recovery machine. (Note: consult factory for mounting packages for other welding tractors).

IMPORTANT FEATURES:

- Ultra lightweight and compact.
- Continuously feeds recovered flux to welding nozzle without need of any transfer valve.
- Slag, dust, and fines are automatically removed from recovered flux.
- No moving parts in air pump. Very efficient air pump produces higher vacuum; uses less air and is much quieter than most competitive models.

OPTIONAL ACCESSORIES:

- RFHM-7 rear hose mounting bracket for LT-7 tractor. Use for fillet welding, or web to flange welds or when welding between tractor wheels.
- NZ 1 CRN corner weld pickup nozzle.
- NZ 1 BUTT butt weld nozzle. (This nozzle drags on plate. Use with FHM - 1 ADJ hose bracket.)
- FHM ADJ hose bracket. Allows NZ - 1 Butt nozzle to follow up / down contours of plate.



XP-3-TRAC-

FOR ORDERING INFORMATION PLEASE CONTACT:

(RFHM-7)

ENGINEERING CO., INC.

34 Fruit St. Shrewsbury, MA 01545 (U.S.A.) Telephone: (508) 842-2224 Fax: (508) 842- 3893

Web Site: weldengineering.com Email: sales@weldengineering.com